



136 South Maple Ave 970-249-7922 p
 Montrose, CO 81401 970-240-6988 f

ECLA METALS L.L.P

Toll Free 1-888-621-0807

www.reclametals.com

RCM Cor4

Panel	Corrugated 4.0 X 15/16"								
Live Load	20 PSF			30 PSF		40 PSF		50 PSF	
	Span	Roof	Wall	Roof	Wall	Roof	Wall	Roof	Wall
22g 180 lbs/sq	1	9'6"	9'10"	8'2"	8'7"	7'2"	7'9"	6'5"	7'3"
	2	9'10"	11'10"	8'1"	9'8"	7'1"	8'4"	6'4"	7'6"
	3	11'0"	12'1"	9'1"	9'1"	7'11"	9'4"	7'1"	8'4"

Notes:

- * Roof loads are for positive loads only and are in addition to weight of panel.
- * Siding loads are for positive or negative loading.
- * Maximum allowable stress for Grade A (F) = 20,000 PSI for roofs and 26,667 PSI for walls where wind is only load.
- * Loads and spans for carbon steel are based on AISI Cold Formed Steel Design Manual.
- * Maximum Allowable Stress (FC) =15,000 PSI, (FT) = 17,000 PSI for roof and side wall. Stresses have been increased 1/3 for wind loading.